

PWR-24/110 / PWR-24/220F / PWR-24/230R



Model: PWR-24/110

Model: PWR-24/220F

Model: PWR-24/230R

Features

PWR-24/110

- Cost-effective power adaptor
- Primary exciting current: Input 110Vac 60 Hz: 60mA
- Primary Load current: Input 110Vac 60 Hz: 52mA
- Secondary no load: DC voltage : 28.6V ; +/- 5%
- Secondary DC voltage: Load 200mA: 24.0V ; +/-5% (4.8AV)
- High protection test:
PRI. TO SEC. & CORE : AC 1240/min
SEC TO CORE : AC 500 V
- Dimensions : 51mm x 41mm x 63mm

PWR-24/220F

- Cost-effective power adaptor
- Input 220Vac 60 Hz: 30mA
- Secondary no load: DC voltage: 29.2V ; +/- 5%
- Secondary DC voltage: Load 100mA: 24.0V ; +/-5% (2.4AV)
- High protection test:
PRI. TO SEC. & CORE : AC 1240/min
SEC TO CORE : AC 500 V
- Dimensions : 51mm x 41mm x 63mm

PWR-24/230R

- Cost-effective power adaptor
- Input 230Vac 50 Hz: 55mA
- Secondary no load:DC voltage: 29.2V ; +/- 5%
- Secondary DC voltage:Load 200mA: 24.0V ; +/-5% (4.8AV)
- High protection test:
PRI. TO SEC. & CORE : AC 1240/min
SEC TO CORE : AC 500 V
- Dimensions : 51 mm x 41 mm x 63 mm

Ordering Information

PWR-24/110 CR	AC 110V input, flat type power adaptor (RoHS)
PWR-24/220F CR	AC 220V input, flat type power adaptor (RoHS)
PWR-24/230R CR	AC 230V input, round type power adaptor (RoHS)